

The Fluke 302+ and 303 come with all the rugged, reliable and accurate features you have come to trust, in a small, ergonomic design. The innovative body design offers a more compact tool to meet your needs. With features of AC current measurements upto 600 A (303), a large 30 mm jaw opening and CAT IV 300 V/CAT III 600 V safety rating, you get an easy-to-use tool that handles your everyday electrical maintenance needs.

### Features

- 600 A AC current measurement (303)
- 400 A DC current measurement (302+)
- Cat IV 300 V/CAT III 600 V safety rated
- 30 mm jaw size for multiple applications
- Resistance range up
- Slim, ergonomic design
- Easy to read backlit display



Specifications			
Function	Parameter	302+	303
AC Current	Range	400.0 A	600.0 A
	Accuracy	1.8% ± 5	1.8% ± 5
AC Voltage	Range	400/600 V	400/600 V
	Accuracy	1.5% ± 5	1.5% ± 5
DC Voltage	Range	400/600 V	400/600 V
	Accuracy	1.0% ± 5	1.0% ± 5
Resistance	Range	4000Ω	4000Ω
Continuity		≤ 70Ω	≤ 70Ω
Backlight Display		Yes	Yes
Data Hold		Yes	Yes
Size	H x W x D (mm)	208 x 58.5 x 28	208 x 58.5 x 28
	Jaw size	30mm	30mm
Safety Rating		CAT III 600V/ CAT IV 300V	CAT III 600V/ CAT IV 300V
Screen Refresh Rate		> 2 times / sec.	> 2 times / sec.
Test Leads		TL75	TL75
Battery		2 AA batteries	2 AA batteries
Warranty		Two years	Two years

### Ordering Information

302+ Clamp Meter

303 Clamp Meter